



Iwan Binanto &lt;binanto.iwan@gmail.com&gt;

## Acceptance Letter: ICICELB-2103-014

1 pesan

office@icicelb.org &lt;office@icicelb.org&gt;

16 April 2021 07.01

Kepada: binanto.iwan@gmail.com

Cc: wbudiharto@binus.edu, spits.hendric@binus.ac.id, nsianipar@binus.edu

Dear Mr. Iwan Binanto,

It is my great pleasure to inform you that your contribution to ICIC Express Letters, Part B: Applications,

Reference No.: ICICELB-2103-014

Title: Mining Frequent Pattern on Liquid Chromatography-Mass Spectrometer Data of Rodent Tuber to Find The Association Rules of Compounds for Machine Learning

Author(s): Iwan Binanto, Widodo Budiharto, Harco Leslie Hendric Spits Warnars and Nesti F. Sianipar

has been accepted for the publication with the following conditions. Also, please use the ICIC-ELB style files <http://www.icicelb.org/ellb/information.html> (either LaTeX source files, or Word with PDF files) for preparing your paper (no more than 8 pages) for the publication.

The paper is generally well written and organized. The results presented in the paper seem correct, and potentially useful in practice. The techniques employed to tackle the problems are generally standard with some novelties. The paper can be accepted for publication subject to some necessary minor changes as below:

Comments:

- 1) The review on existing studies is not enough. It has been found that no reviewed references in the Introduction are published in recent three years; therefore, the motivation of this work, that is, why to explore mining pattern on Rodent Tuber's LC-MS data, will be limited.
- 2) In the Introduction, the advantages of this study compared with the existing relevant studies should be highlighted, and the results obtained from this study should also be stated.
- 3) The caption of Figure 2 is suggested to be improved as "Diagram of research method".
- 4) Below Figure 5, authors mentioned the next step is dataset processing with form as a market basket transaction; however, what is the corresponding step in Figure 2?
- 5) To prove the effectiveness of the proposed system, a comparison with state-of-the-art studies is suggested to be added.
- 6) Not enough recently published references are cited in the manuscript; therefore, it is suggested to cite more up-to-date references from mainstream journals, for example, the paper titled "A Parallel Method for Mining Frequent Patterns with Multiple Minimum Support Thresholds" in International Journal of Innovative Computing, Information and Control, vol.15, no.2, pp.479-488, DOI: 10.24507/ijicic.15.02.479, 2019.
- 7) There are several ill-formed expressions existing in the manuscript, which need further improvement, such as "It find C49H79O13P is the dominant in the LC-MS data", "it is not generate candidate itemsets", "These papers are categorized as follow", "...in Python programming for generate sample" and "This process is conversion dataset to the form of market basket transaction as illustrated in Figure 4A and snippet the real result dataset of this conversion is shown".

Please note that if the paper is not revised satisfactorily complying with the conditions above, ICIC-ELB reserves the right to reject the paper from the journal.

Please submit your Final Version, Revision Note, the Publication Page Charges and Copyright Form (<http://www.icicelb.org/ellb/information.html>) to us within Three Weeks' Time (from the date of this message) at our online submission system <http://www.icicelb.org>. Thank you for your understanding and cooperation.

ICIC-ELB has been indexed in Scopus (Elsevier), and INSPEC (IET). We would like you to refer to ICIC-ELB publications especially your own works in your future research. We believe it will help you promote your article and enhance its visibility.

Please feel free to contact me if you have any questions about your paper.

Best Regards,  
Dr. Yan SHI  
Editor-in-Chief, ICIC-ELB  
Professor, School of Industrial and Welfare Engineering, Tokai University  
9-1-1, Toroku, Kumamoto 862-8652, Japan  
Tel.: 81-96-386-2666, Fax: 81-96-386-2666  
E-mail: [office@icicelb.org](mailto:office@icicelb.org)

**ICIC Express Letters, Part B: Applications**  
*(An International Journal of Research and Surveys)*

**Author's Warranty and Assignment of Copyright**

Dear Contributor(s),

We are pleased that you are contributing a paper to the **ICIC Express Letters, Part B: Applications** -- *An International Journal of Research and Surveys* (ICIC-ELB). State the complete title and all authors of the contribution, read the agreement, sign and return it to the ICIC-ELB Office on the online submission system.

**Paper ID: ICICELB-2103-014**

**Full title of paper:**

**Mining Frequent Pattern on Liquid Chromatography-Mass Spectrometer Data of Rodent Tuber to Find The Association Rules of Compounds for Machine Learning**

**Author(s) (Full names):**

Iwan Binanto  
Harco Leslie Hendric Spits Warnars  
Nesti Fronika Sianipar  
Widodo Budiharto

Your submission of this work and our acceptance for publication are contingent upon your warranty of the following conditions which constitute the Agreement between the author(s) and the ICIC International.

You warrant that the above titled contribution is original, has not been published elsewhere or has not been submitted for publication elsewhere. You warrant that it does not contain libelous material. You agree to transfer copyright to the ICIC International upon acceptance for publication. If the article contains material copyrighted by others, the author warrants that written permission has been obtained from copyright holders who agree to transfer copyright to the extent allowable.

Please indicate your agreement with these terms by signing and dating below.

**Author(s) Signature:**  **Date: 20 April 2021**

**Please sign and return this form promptly**

**It is necessary to sign and return this Author's Warranty and Assignment of Copyright in order to publish your contribution**

**Return Copyright form on the submission system**



Iwan Binanto &lt;binanto.iwan@gmail.com&gt;

---

**Acceptance Letter: ICICELB-2103-014**

1 pesan

**office@icicelb.org** <office@icicelb.org>

16 April 2021 07.01

Kepada: binanto.iwan@gmail.com

Cc: wbudiharto@binus.edu, spits.hendric@binus.ac.id, nsianipar@binus.edu

Dear Mr. Iwan Binanto,

It is my great pleasure to inform you that your contribution to ICIC Express Letters, Part B: Applications,

Reference No.: ICICELB-2103-014

Title: Mining Frequent Pattern on Liquid Chromatography-Mass Spectrometer Data of Rodent Tuber to Find The Association Rules of Compounds for Machine Learning

Author(s): Iwan Binanto, Widodo Budiharto, Harco Leslie Hendric Spits Warnars and Nesti F. Sianipar

has been accepted for the publication with the following conditions. Also, please use the ICIC-ELB style files <http://www.icicelb.org/ellb/information.html> (either LaTeX source files, or Word with PDF files) for preparing your paper (no more than 8 pages) for the publication.

The paper is generally well written and organized. The results presented in the paper seem correct, and potentially useful in practice. The techniques employed to tackle the problems are generally standard with some novelties. The paper can be accepted for publication subject to some necessary minor changes as below:

Comments:

- 1) The review on existing studies is not enough. It has been found that no reviewed references in the Introduction are published in recent three years; therefore, the motivation of this work, that is, why to explore mining pattern on Rodent Tuber's LC-MS data, will be limited.
- 2) In the Introduction, the advantages of this study compared with the existing relevant studies should be highlighted, and the results obtained from this study should also be stated.
- 3) The caption of Figure 2 is suggested to be improved as "Diagram of research method".
- 4) Below Figure 5, authors mentioned the next step is dataset processing with form as a market basket transaction; however, what is the corresponding step in Figure 2?
- 5) To prove the effectiveness of the proposed system, a comparison with state-of-the-art studies is suggested to be added.
- 6) Not enough recently published references are cited in the manuscript; therefore, it is suggested to cite more up-to-date references from mainstream journals, for example, the paper titled "A Parallel Method for Mining Frequent Patterns with Multiple Minimum Support Thresholds" in International Journal of Innovative Computing, Information and Control, vol.15, no.2, pp.479-488, DOI: 10.24507/ijicic.15.02.479, 2019.
- 7) There are several ill-formed expressions existing in the manuscript, which need further improvement, such as "It find C49H79O13P is the dominant in the LC-MS data", "it is not generate candidate itemsets", "These papers are categorized as follow", "...in Python programming for generate sample" and "This process is conversion dataset to the form of market basket transaction as illustrated in Figure 4A and snippet the real result dataset of this conversion is shown".

Please note that if the paper is not revised satisfactorily complying with the conditions above, ICIC-ELB reserves the right to reject the paper from the journal.

Please submit your Final Version, Revision Note, the Publication Page Charges and Copyright Form (<http://www.icicelb.org/ellb/information.html>) to us within Three Weeks' Time (from the date of this message) at our online submission system <http://www.icicelb.org>. Thank you for your understanding and cooperation.

ICIC-ELB has been indexed in Scopus (Elsevier), and INSPEC (IET). We would like you to refer to ICIC-ELB publications especially your own works in your future research. We believe it will help you promote your article and enhance its visibility.

Please feel free to contact me if you have any questions about your paper.

Best Regards,  
Dr. Yan SHI  
Editor-in-Chief, ICIC-ELB  
Professor, School of Industrial and Welfare Engineering, Tokai University  
9-1-1, Toroku, Kumamoto 862-8652, Japan  
Tel.: 81-96-386-2666, Fax: 81-96-386-2666  
E-mail: [office@icicelb.org](mailto:office@icicelb.org)

## MINING FREQUENT PATTERN ON LIQUID CHROMATOGRAPHY-MASS SPECTROMETER DATA OF RODENT TUBER TO FIND THE ASSOCIATION RULES OF COMPOUNDS FOR MACHINE LEARNING

IWAN BINANTO<sup>1,2</sup>, HARCO LESLIE HENDRIC SPITS WARNARS<sup>1</sup>  
NESTI FRONIKA SIANIPAR<sup>3,4</sup> AND WIDODO BUDIHARTO<sup>1</sup>

<sup>1</sup>Computer Science Department, BINUS Graduate Program – Doctor of Computer Science

<sup>3</sup>Food Technology Department, Faculty of Engineering

<sup>4</sup>Research Interest Group Biotechnology

Bina Nusantara University

Jl. K. H. Syahdan No. 9, Kemanggisian, Palmerah, Jakarta 11480, Indonesia

binanto.iwan@gmail.com; spits.hendric@binus.ac.id; {nsianipar; wbudiharto}@binus.edu

<sup>2</sup>Informatics Department

Sanata Dharma University

Yogyakarta, Indonesia

Received March 2021; accepted June 2021

**ABSTRACT.** *Liquid Chromatography-Mass Spectrometry (LC-MS) data contains a lot of measurement data, which contains Rodent Tuber plant measurement. This paper aims to obtain frequent patterns on LCMS data utilizing the FP-Growth method, where frequent patterns will be used for interpretation and identification of chemical compound in a biological sample. For faster computation, it needed representative sampling data and linear systematic sampling was utilized for this purpose. In conclusion, FP-Growth can be applied successfully on Rodent Tuber's sample LC-MS data and generate an association rule of chemical compound formula. The result showed that C<sub>49</sub>H<sub>79</sub>O<sub>13</sub>P was the dominant compound in the LC-MS data with the highest support value of 41.67%. However, it depends on the other, namely [C<sub>43</sub>H<sub>49</sub>O<sub>23</sub>]<sup>+</sup>. It can be said that when [C<sub>43</sub>H<sub>49</sub>O<sub>23</sub>]<sup>+</sup> appears, there is possibility that C<sub>49</sub>H<sub>79</sub>O<sub>13</sub>P will also appear. Also, there is a perfect rule that [C<sub>43</sub>H<sub>49</sub>O<sub>23</sub>]<sup>+</sup> implies C<sub>49</sub>H<sub>79</sub>O<sub>13</sub>P but not conversely. These results can be utilized for rule-based machine learning.*

**Keywords:** LC-MS, Frequent pattern growth, Rodent Tuber, Data mining, Linear systematic sampling, Machine learning

1. **Introduction.** Raw data of Liquid Chromatography-Mass Spectrometry (LC-MS) contains millions of data points, and there are hundreds to thousands of chromatographic peaks, after integration and peak extraction [1]. This raw data provide highly complex biological samples [2]. Meanwhile, LC-MS is widely used, especially in the interpretation or identification of the content of chemical compounds in a biological sample [2-6]. It consists of hundreds of thousands of mass per charge (m/z), retention time, and intensity [7]. Likewise, the LC-MS data of Rodent Tuber from the studies of Sianipar et al. [8-12] which is used in this paper.

It is not trivial to processing this data to be useful information. Many techniques are used to process these data. It is challenging to extract the information contained in the LC-MS data. One of them is finding certain patterns in the data with association rule. This pattern can be used to find and recognize certain chemical compounds contained in other LC-MS data. Further, the association rule can be used in machine learning.

Association rule is a standardized and well-researched technique for finding interesting relationships between variables [13], finding causalities between variables [14], finding the frequent patterns in large databases [15,16], and feature selection for classification [17]. The association rule is obtained by searching the frequent itemset of all frequent itemsets in the database. The discovery of frequent itemset is an important step in obtaining association rule [18]. Two algorithms are popular in this field, namely Apriori and FP-Growth which are mining frequent patterns from a set of transactions in horizontal data format [19], although utilize only one minimum support threshold [20].

FP-Growth was chosen because of its popularity [16], with a moderate time complexity and space complexity [21], among the best ones to extract association patterns of the frequent item sets [22], and advantages such as more efficient than Apriori and adopting divide and conquer strategy as discussed in [13,15,23-25].

This paper describes pattern mining on Rodent Tuber’s LC-MS data to obtain association rules to determine the relationships and/or casualities between chemical compounds. The results of this study will help biological or pharmaceutical scientists to 1) analyze and identify the possible presence of other compounds, 2) find interesting relationships and/or casualities between compounds, 3) find the frequent patterns, and 4) can be used for further processing in machine learning.

This paper categorized as follows. Section 2 describes the problem statement and preliminaries process for further processing. Section 3 describes the research method. Section 4 describes the result and discussion. Section 5 focuses on conclusions and future work.

**2. Problem Statement and Preliminaries.** LC-MS data contain a huge number of compounds. It is possible to identify compounds that frequently occur and their association with other compounds. It can be established as a pattern for other purposes.

There are more than 700,000 records in each of LC-MS data of Rodent Tuber from studies of Sianipar et al. [8-12]. Their studies resulted in 10 datasets. We have calculated, to get one compound name manually, will take about 20 seconds at the fastest time. By a simple calculation, about 700,000 records will take  $20 \times 700,000$  seconds. That means 5 months to complete the labeling for each dataset.

Using large native data like this case would be expensive. Therefore, data sampling will be carried out. This LC-MS data of Rodent Tuber is time-series data, so it is required sampling per period to obtain a representative sample that represents the actual dataset. Linear systematic sampling is chosen because it is simple and can represent the actual dataset.

To obtain a systematic sample, given that  $N$  is the number of population of elements, while  $n$  is the number of samples desired, so if  $N/n$  is an integer, then  $k = N/n$ ; otherwise, let  $k$  be the next integer after  $N/n$ .

After that, find a random integer  $R$  between 1 and  $k$ , defining the sample as the unit numbered  $R, R + k, R + 2k$ , and so on. The initial unit  $R$  selected is called “random start” and  $k$  is called “sampling interval” [26,27].

Based on that, we develop Algorithm 1 as shown in Figure 1 and it is implemented in python. It is applied to one of ten of the LC-MS dataset of Rodent Tuber which we have and the result will be used in this paper.

**3. Research Method.** Our research method consists of several stages as shown in Figure 2. Preliminaries above are the first stage of this method as preparation and initial stage by implementing Algorithm 1 as shown in Figure 1 utilizing linear systematic sampling. This preliminary generates a representative sample of the whole dataset. It generates 18,271 records out of 985,924 records.

**Algorithm 1:** LSS

---

```

Result: Sample File in type .xlsx
df = pd.read_excel(file)
listDF = df.values.tolist()
pivotDF = pd.pivot_table(df,index = ["Retention Time"])
arrRT = pivotDF.index.array.to_numpy()
arrSample = [ ]
arrTempRT = [ ]
arrTempI = [ ]
totalRec = 0
k = len(listDF)/18000
for n in range(len(arrRT)):
    arrTemp = [ ]
    arrTempInt = [ ]
    for i in range(len(listDF)):
        if listDF[i][2] == arrRT[n]:
            arrTemp.append(listDF[i][0])
            arrTempInt.append(listDF[i][1])
        indexes = np.arange(random.randint(0,k),
                            len(arrTemp), step = k)
    for i in indexes:
        arrSample.append(arrTemp[i])
        arrTempRT.append(arrRT[n])
        arrTempI.append(arrTempInt[i])
df1.to_excel('sampleFile.xlsx', index = False)

```

---

FIGURE 1. Algorithm of linear systematic sampling




FIGURE 2. Diagram of research method

FP-Growth is commonly used for market basket analysis which usually has data label. The LCMS data to be analyzed does not have label, so it needs to be labeled. Labeling in this study is giving name of chemical compounds based on their mass per charge ( $m/z$ ) in the data. After labeling, the LCMS data will be converted into a kind of transactional



data like a market basket transaction. It is labeled with another previously developed tool in stage “Data Labeling”.

The result of labeling is an unclean dataset as shown in Figure 3(a), because there are several missing names of chemical compounds; in this case, we write it with characters “-”. Therefore, “Data Cleaning and Fitting” was carried out. Data cleaning and fitting is intended to dispose empty data or has no label. It generates dataset as shown in Figure 3(b).

5.022	139408	54.743965	0.00	-	-	5.022	314416	82.195719	82.0531	C4H6N2	2-Methylimidazole
5.022	314416	82.195709	82.0531	C4H6N2	2-Methylimidazole	5.022	164000	157.34001	157.16901	C7H11NO3	Acetylproline
5.022	49996	105.536	0.00	-	-	5.022	83488	180.99664	181.00198	C8H7NS2	2-(Methylsulfanyl)-1,3-benzothiazole
5.022	140672	130.6474	0.00	-	-	5.022	208448	204.9695	205.03751	C10H7NO4	Xanthurenic acid
5.022	164000	157.34009	157.16901	C7H11NO3	Acetylproline	5.022	114944	232.2947	232.2847	C13H16N2O2	3-Dimethylaminoacetyl-5-methoxyindole
5.022	83488	180.99664	181.00198	C8H7NS2	2-(Methylsulfanyl)-1,3-benzothiazole	5.022	78616	255.888	256.00415	C10H8O6S	4-Methylumbelliferyl sulfate
5.022	208448	204.96948	205.03751	C10H7NO4	Xanthurenic acid	5.022	53868	299.59576	299.3786	C20H17N3	Komarovicine
5.022	114944	232.29471	232.2847	C13H16N2O2	3-Dimethylaminoacetyl-5-methoxyindole	5.022	29919	322.5565	322.41049	C20H22N2O2	Haplamidine
5.022	78616	255.88803	256.00415	C10H8O6S	4-Methylumbelliferyl sulfate	5.022	20764	341.15289	341.14749	C16H23NO7	Monocrotaline N-oxide
5.022	70692	278.78558	0.00	-	-	5.022	31190	368.1618	368.12598	C21H20O6	Curcumin
5.022	53868	299.59576	299.3786	C20H17N3	Komarovicine	5.022	20871	462.0291	462.0798	C21H18O12	Scutellarein-7- $\beta$ -glucuronide
5.022	29919	322.55652	322.41049	C20H22N2O2	Haplamidine	5.022	4040	544.4475	544.59698	C29H36O10	10-Deacetyl baccatin III
5.022	20764	341.15289	341.14749	C16H23NO7	Monocrotaline N-oxide	5.022	12046	597.95947	0.00	-	-
5.022	31190	368.1618	368.12598	C21H20O6	Curcumin	5.022	9886	683.66699	0.00	-	-
5.022	25493	395.42383	395.3399	C24H45NO3	N-Oleoyl-isooleucine	5.022	36472	733.38379	733.46124	C37H67NO13	Erythromycin
5.022	14206	427.99902	428.01309	C15H19Cl3N2O4S	PRZ_M429	5.022	17375	798.1547	798.16431	C37H67NO13	Erythromycin
5.022	20871	462.02905	462.0798	C21H18O12	Scutellarein-7- $\beta$ -glucuronide	5.022	191	821.2419	821.08801	C46H77O10P	PG 40:7
5.022	27615	494.98376	0.00	-	-	5.022	191	844.8986	845.10999	C48H77O10P	PG 40:9
5.022	4040	544.44751	544.59698	C29H36O10	10-Deacetyl baccatin III	5.022	191	914.5399	914.58844	C49H87O13P	Phosphatidylinositol 18:0-22:4
5.022	12046	597.95947	0.00	-	-	5.022	191	958.7537	958.51367	C48H78O19	3-Glc-Gal-Glc-UeA-Soyasapogenol B
5.022	9886	683.66699	0.00	-	-	5.022	265	1029.344	1029.18005	C51H80O21	Soyasapogenol B + d-Hex + Hex + malonyl
5.022	36472	733.38379	733.46124	C37H67NO13	Erythromycin	5.022	191	1103.097	1103.25903	C54H86O23	Soyasapogenol B base + O-d-Hex + O-Hex-A-Hex-d-Hex
5.022	17375	798.15466	798.16431	C37H67NO13	4'-O-[2'-E-Feruloyl GluA(1-2)GluA] Apigenin (NMR)	10.045	12949	163.2226	163.24001	C6H13NO2S	(3R)-3-amino-5-methylsulfanyl-pentanoic acid, R-3-A...
5.022	191	821.24194	821.08801	C46H77O10P	PG 40:7	10.045	8657	191.1804	191.186	C10H9NO3	5-Hydroxyindole-3-acetate, 5-HIAA, 5-Oxyindoleace...
5.022	191	844.89856	845.10999	C48H77O10P	PG 42:9	10.045	71648	216.7978	217.00612	C9H9Cl2NO	Propanil
5.022	191	878.80212	0.00000	-	-						

(a)

(b)

FIGURE 3. (a) Snippet unclean data; (b) snippet cleaning and fitting result

After the dataset is cleaned and fit according to what we want, it needs to be processed again to adjust the use of the FP-Growth algorithm. We called it “Convert to Transactional Form”.

This process converts the dataset to the transactional form as a market basket transaction as illustrated in Figure 4(a) and the snippet of real result dataset of this conversion is shown in Figure 4(b). In this case, Transaction ID (TID) is Retention Time and the item set is compound formula. It is done by Algorithm 2 as seen in Figure 5. Retention Time is a TID because it has many duplicates with different m/z, as in actual case, a grocery receipt consisting of many shopping items with one TID which actually can be interpreted that there are many duplicates of TID because it is attached to one item which is then summarized into one.

<b>ID</b>	<b>Items</b>					
1	{Bread, Milk}					
2	{Bread, Diapers, Beer, Eggs}					
3	{Milk, Diapers, Beer, Cola}					
4	{Bread, Milk, Diapers, Beer}					
5	{Bread, Milk, Diapers, Cola}					
...	...					
	{Diapers, Beer}	Example of a frequent itemset				
	{Diapers} $\rightarrow$ {Beer}	Example of an association rule				

} market basket transactions

C4H6N2	C7H11NO3	C8H7NS2	C10H7NO4	C13H16N2O2	C10H8O6S	C20H17N3
C6H13NO2S	C6H13NO2S	C10H9NO3	C10H9NO3	C10H9NO3	C9H9Cl2NO	[C15H11O6] <sup>+</sup>
C4H7NO2	C7H6O2	C5H6O5	C7H3Cl2N	C10H13NO3	C9H15NO3S	C16H35N
C5H5N	C3H7NO6S	C8H7NO4S	C6H13O8P	C18H34O2	C18H34O2	C18H34O2
C4H8N2O	C3H8O3S	C7H5NO5	C10H8O4	C14H17NO	C15H11NO2	C16H34O2
CH4O3S	CH4O3S	CH4O3S	CH4O3S	C6H12N2O	C4H6N4O3	C8H8Cl2N2O
C5H4N4O	C8H7NO3	C6H3Cl2NO2	C9H9Cl2NO	C6H12N2O4S2	C15H18O4	C6H8ClN3O4S2
C3H9NO	C3H9NO	C3H9NO	C3H9NO	C3H4O5	C7H5NO5	C11H19NO5
C5H5N	C3H6O2S	C10H16	C10H16	C9H8O3	C8H8N2O3S	C9H1Cl2N2O
C3H4N4O2	C3H7O7P	C14H31N	C20H36O2	C15H17Cl2N3O2	C14H17N2O2	C22H23N5O3
C5H5NO	C4H6O5	C4H5NO4S	C9H10ClNO3	C12H18N2O3	C6H15O9P	C14H24N2O4
C3H7NO3	C8H5NO2	C7H8N4O2	C7H8N4O2	C7H8N4O2	C7H5NO3S2	C14H16N2O2
C3H7NO	C4H6O5	C8H18N2O	C13H22O	C13H22O	C12H15NO3	C9H16N2O6
C4H7NO2	C4H7NO2	C5H6O5	C9H21N3O	C8H6Cl2O3	C10H9Cl2N3O	C19H28O2
C2H5NO3	C2H5NO3	C2H5NO3	C2H5NO3	C4H6O5	C6H6O3S	C10H10O6
C4H4N2	C4H4N2	C4H4N2	C4H4N2	C6H5NO2	C6H6O3S	C7H4Cl2O2
C3H4O5	C6H11NO4	C6H11NO4	C6H11NO4	C5H2Cl3NO	C12H11NO2S	C8H4Cl3NO3

(a)

(b)

FIGURE 4. (a) Illustration of market basket transactions [28]; (b) snippet data

The next step is “Run FP-Growth Algorithm” which is processing the transactional form as a market basket transaction into FP-Growth algorithm. This aims to find the frequent pattern of item. This algorithm is implemented in the python library namely mlxtend.frequent\_patterns [29]. We just used it without adjustment of anything.

---

**Algorithm 2:** Convert to market basket transaction

---

- 1: Get data from the dataset that has been made into an excel file and convert it to an actual data list, namely listDF[].
  - 2: Create a list that contains “Retention Time” column without duplication with the pivot feature, namely arrRT[].
  - 3: rows, cols = (len(arrRT), len(listDF))  
arr = [ ]
  - 4: for  $i$  in range(rows):  
    row = [ ]  
    for  $j$  in range (cols):  
        if listDF[j][4] == arrRT[i]:  $\Rightarrow$  check same Retention Time  
            row.append(listDF[j][1])  $\Rightarrow$  append Formula to new list as row
  - 5: arr.append(row)  $\Rightarrow$  appen list ROW in list ARR  
Write arr[] list into an excel file.  $\Rightarrow$  result is 2D list
- 

FIGURE 5. Algorithm of conversion to market basket transaction

4. **Result and Discussion.** Linear systematic sampling successfully builds a sample of LC-MS data which at first contains 985,924 records to 18,271 records done by Algorithm 1. Using a smaller number of data sample but representing the entire dataset, labeling work is faster. Labeling was done by web scraping technique [30-32]. The next steps are cleaning and fitting, converting, and processed to FP-Growth algorithm. All processes are implemented in python programming and FP-growth library.

The results of FP-Growth processing with minimum support of 35% are shown in Figure 6(a) and the association rule with a minimum threshold of 35% is shown in Figure 6(b).

	support	itemsets
0	0.416667	(C49H79O13P)
1	0.361111	(C50H86NO8P)
2	0.361111	(C48H76O18)
3	0.361111	([C43H49O23]+)
4	0.361111	(C48H78O18)
5	0.361111	([C43H49O23]+, C49H79O13P)

(a)

	antecedents	consequents	antecedent support	consequent support	support	confidence	lift	leverage	conviction
0	([C43H49O23]+)	(C49H79O13P)	0.361111	0.416667	0.361111	1.000000	2.4	0.210648	inf
1	(C49H79O13P)	([C43H49O23]+)	0.416667	0.361111	0.361111	0.866667	2.4	0.210648	4.791667

(b)

FIGURE 6. (a) Result of FP-Growth; (b) result of association rule

As seen in Figure 6(a), the highest support is 0.416667 and it is a single item, which is C49H79O13P, namely Phosphatidylinositol 20:4-20:4 with exact mass is 906.52582; it means this item appears most frequently (41.6%) in the data. It is dominant compared with others.

In Figure 6(b), the highest confidence value is 1.00, this can be interpreted that if there is [C43H49O23]+, then absolutey C49H79O13P exists, but if conversely, the confidence value is smaller (86.67%) which is still a good value because of more than 50%. This result has an association with lift value which is more than 1. They are dependent on each other as can be seen in the leverage value which is more than 0.

The conviction will be infinity ( $\infty$ ) if a perfect rule and has a value of 1 if it is a completely uncorrelated rule [33].  $[C43H49O23]^+$  implies  $C49H79O13P$  has conviction infinity which means that this is a perfect rule of the antecedent ( $[C43H49O23]^+$ ) to the consequent ( $C49H79O13P$ ) but not conversely.

5. **Conclusion.** The FP-Growth algorithm using python library namely `mlxtend.frequent_patterns` can be applied well to the sample of LC-MS data of Rodent Tuber. Sampling was done by the linear systematic sampling method. It serves to simplify a huge dataset but still reflects the actual dataset.

There is a huge number of compounds in LC-MS data of Rodent Tuber when closely observed. However, by processing the dataset with FP-Growth, it can be seen which compounds are more dominant than others. As seen from Figure 6(a), the highest support value is 41.67% which is  $C49H79O13P$ . It can be interpreted that  $C49H79O13P$  is the dominant compound in this LC-MS data. However, this compound depends on other compounds, namely  $[C43H49O23]^+$  which can be seen in Figure 6(b) with an infinity conviction value. It can also be said that when  $[C43H49O23]^+$  appears, absolutely  $C49H79O13P$  will also appear. These association rules can be utilized for processing with rule-based machine learning.

For future works, this study will be applied to other datasets from the existing LC-MS data of Rodent Tuber so that more comprehensive results are obtained.

## REFERENCES

- [1] P. Kharyuk et al., Employing fingerprinting of medicinal plants by means of LC-MS and machine learning for species identification task, *Sci. Rep.*, vol.8, no.1, pp.1-12, DOI: 10.1038/s41598-018-35399-z, 2018.
- [2] M. Brown et al., Automated workflows for accurate mass-based putative metabolite identification in LC/MS-derived metabolomic datasets, *Bioinformatics*, vol.27, no.8, pp.1108-1112, DOI: 10.1093/bioinformatics/btr079, 2011.
- [3] M. Gerlich and S. Neumann, MetFusion: Integration of compound identification strategies, *J. Mass Spectrom.*, vol.48, no.3, pp.291-298, DOI: 10.1002/jms.3123, 2013.
- [4] C. Guijas et al., METLIN: A technology platform for identifying knowns and unknowns, *Anal. Chem.*, vol.90, no.5, pp.3156-3164, DOI: 10.1021/acs.analchem.7b04424, 2018.
- [5] B. Zhou, J. F. Xiao, L. Tuli and H. W. Ransom, LC-MS-based metabolomics, *Mol. Biosyst.*, vol.8, no.2, pp.470-481, DOI: 10.1039/C1MB05350G, 2012.
- [6] J. Listgarten and A. Emili, Statistical and computational methods for comparative proteomic profiling using liquid chromatography-tandem mass spectrometry, *Mol. Cell. Proteomics*, vol.4, no.4, pp.419-434, DOI: 10.1074/mcp.R500005-MCP200, 2005.
- [7] F. Fernández-Albert, *Machine Learning Methods for the Analysis of Liquid Chromatography-Mass Spectrometry Datasets in Metabolomics*, Universitat Polit' Ecnica De Catalunya, 2014.
- [8] D. Laurent, N. F. Sianipar, Chelen, Listiari and A. Wantho, Analysis of genetic diversity of Indonesia rodent tuber (*Typhonium flagelliforme* Lodd.) cultivars based on RAPD marker, *The 3rd International Conference on Biological Science (ICBS-2013)*, vol.2, pp.139-145, 2015.
- [9] N. F. Sianipar, R. Purnamaningsih and Rosaria, Bioactive compounds of fourth generation gamma-irradiated *Typhonium flagelliforme* Lodd. mutants based on gas chromatography-mass spectrometry, *IOP Conf. Ser.: Earth Environ. Sci.*, vol.41, DOI: 10.1088/1755-1315/41/1/012025, 2016.
- [10] N. F. Sianipar, R. Purnamaningsih, D. L. Gumanti, Rosaria and M. Vidiанти, Analysis of gamma irradiated-third generation mutants of rodent tuber (*Typhonium flagelliforme* Lodd.) based on morphology, RAPD, and GC-MS markers, *Pertanika J. Trop. Agric. Sci.*, vol.40, no.1, pp.185-202, 2017.
- [11] N. F. Sianipar and R. Purnamaningsih, Molecular detection of putative mutant clones of rodent tuber (*Typhonium flagelliforme* Lodd.) CV. pekanlongan using RAPD markers, *Malays. Appl. Biol.*, vol.47, no.2, pp.1-8, 2018.
- [12] N. F. Sianipar, K. Assidqi, R. Purnamaningsih and T. Herlina, Vitro cytotoxic activity of rodent tuber mutant plant (*Typhonium flagelliforme* Lodd.) against to MCF-7 breast cancer cell line, *Asian J. Pharm. Clin. Res.*, vol.12, no.3, pp.185-189, DOI: 10.22159/ajpcr.2019.v12i3.29651, 2019.
- [13] M. S. Mythili and A. R. M. Shanavas, Performance evaluation of Apriori and FP-growth algorithms, *Int. J. Comput. Appl.*, vol.79, no.10, pp.34-37, DOI: 10.5120/13779-1650, 2013.

- [14] S. Lee, Y. Cha, S. Han and C. Hyun, Application of association rule mining and social network analysis for understanding causality of construction defects, *Sustain.*, vol.11, no.3, DOI: 10.3390/su11030618, 2019.
- [15] M. Kavitha and S. T. T. Selvi, Comparative study on Apriori algorithm and FP growth algorithm with pros and cons, *Int. J. Comput. Sci. Trends Technol. (IJCST)*, vol.4, no.4, pp.161-164, 2013.
- [16] S. Nasreen, M. A. Azam, K. Shehzad, U. Naeem and M. A. Ghazanfar, Frequent pattern mining algorithms for finding associated frequent patterns for data streams: A survey, *Procedia Comput. Sci.*, vol.37, pp.109-116, DOI: 10.1016/j.procs.2014.08.019, 2014.
- [17] C. Huang et al., Sample imbalance disease classification model based on association rule feature selection, *Pattern Recognit. Lett.*, vol.133, pp.280-286, DOI: 10.1016/j.patrec.2020.03.016, 2020.
- [18] S. Bagui, K. Devulapalli and J. Coffey, A heuristic approach for load balancing the FP-Growth algorithm on MapReduce, *Array*, vol.7, DOI: 10.1016/j.array.2020.100035, 2020.
- [19] A. Mokkaem, M. Pelletier and L. Raimbault, Recursive association rule mining, *arXiv.org*, arXiv: 2011.14195, 2020.
- [20] B. Huynh, C. Trinh, V. Dang and B. Vo, A parallel method for mining frequent patterns with multiple minimum support thresholds, *International Journal of Innovative Computing, Information and Control*, vol.15, no.2, pp.479-488, 2019.
- [21] X. Gao, M. Sun, C. He and Y. Jia, Assisted analysis of acne metagenomics sequencing data based on FP-Growth method, *2019 the 3rd International Conference on Electronic Information Technology and Computer Engineering (EITCE)*, DOI: 10.1109/EITCE47263.2019.9094872, pp.1711-1714, 2019.
- [22] S. J. Nejad, F. Ahmadi-Abkenari and P. Bayat, A combination of frequent pattern mining and graph traversal approaches for aspect elicitation in customer reviews, *IEEE Access*, vol.8, pp.151908-151925, DOI: 10.1109/ACCESS.2020.3017486, 2020.
- [23] F. Xu and H. Lu, The application of FP-Growth algorithm based on distributed intelligence in wisdom medical treatment, *Int. J. Pattern Recognit. Artif. Intell.*, vol.31, no.4, pp.1-11, DOI: 10.1142/S0218001417590054, 2017.
- [24] P. Shendge and T. Gupta, Comparative study of apriori & FP growth algorithms, *Indian J. Res.*, no.3, pp.20-22, 2013.
- [25] M. Narvekar and S. F. Syed, An optimized algorithm for association rule mining using FP tree, *Procedia Comput. Sci.*, vol.45, pp.101-110, DOI: 10.1016/j.procs.2015.03.097, 2015.
- [26] R. Arnab, Systematic sampling, in *Survey Sampling Theory and Applications*, R. Arnab (ed.), Academic Press, 2017.
- [27] S. L. Lohr, *Sampling: Design and Analysis*, 2nd Edition, Brooks/Cole, Cengage Learning, Boston, 2010.
- [28] *Market Basket Analysis Using R – DataCamp*, <https://www.datacamp.com/community/tutorials/market-basket-analysis-r>, Accessed on Nov. 27, 2020.
- [29] *Mlxtend.frequent Patterns – mlxtend*, [http://rasbt.github.io/mlxtend/api\\_subpackages/mlxtend.frequent\\_patterns/](http://rasbt.github.io/mlxtend/api_subpackages/mlxtend.frequent_patterns/), Accessed on Nov. 27, 2020.
- [30] M. Herrmann and L. Hoyden, Applied webscraping in market research, *The 1st International Conference on Advanced Research Methods and Analytics*, DOI: 10.4995/carma2016.2016.3131, 2016.
- [31] M. Shreesha, S. B. Srikara and R. Manjesh, A novel approach for news extraction using webscraping technique, *The 3rd National Conference on Image Processing, Computing, Communication, Networking and Data Analytics (NCICCNDA2018)*, DOI: 10.21467/proceedings.1.56, pp.359-362, 2018.
- [32] R. McAlister, Webscraping as an investigation tool to identify potential human trafficking operations in Romania, *Proc. of 2015 ACM Web Sci. Conf.*, DOI: 10.1145/2786451.2786510, 2015.
- [33] S. Brin, R. Motwani, J. D. Ullman and S. Tsur, Dynamic itemset counting and implication rules for market basket data, *SIGMOD Rec. (ACM Spec. Interes. Gr. Manag. Data)*, vol.26, no.2, pp.255-264, DOI: 10.1145/253262.253325, 1997.



Iwan Binanto &lt;binanto.iwan@gmail.com&gt;

**Invoice-Letter (ICICELB-2103-014)**

1 pesan

**office@icicelb.org** <office@icicelb.org>

16 April 2021 07.01

Kepada: binanto.iwan@gmail.com

Cc: wbudiharto@binus.edu, spits.hendric@binus.ac.id, nsianipar@binus.edu

**ICIC Express Letters, Part B: Applications****An International Journal of Research and Surveys**

2021-04-16

INVOICE (No. ICICELB-2103-014)

Mr. Iwan Binanto  
Sanata Dharma University  
Indonesia  
[binanto.iwan@gmail.com](mailto:binanto.iwan@gmail.com)

Publication Page Charges for:

Reference No.: ICICELB-2103-014

Title: Mining Frequent Pattern on Liquid Chromatography-Mass Spectrometer Data of Rodent Tuber to Find The Association Rules of Compounds for Machine Learning

Author(s): Iwan Binanto, Widodo Budiharto, Harco Leslie Hendric Spits Warnars and Nesti F. Sianipar

in (ICIC Express Letters, Part B: Applications -- An International Journal of Research and Surveys, ISSN 2185-2766) as a publication, which will generally be published within 6 months thereafter.

Amount due: JPY48,000 (no more than 8 pages)

Please complete the following form and return it to the ICIC-ELB Editorial Office together with your final version on the submission system.

Credit Card:  Visa  MasterCard

Credit Card No.: \_\_\_\_\_/\_\_\_\_\_/\_\_\_\_\_/\_\_\_\_\_

Expiry Date: \_\_\_\_\_month/\_\_\_\_\_year

Card Holder's Name: \_\_\_\_\_

Authorized Signature: \_\_\_\_\_

Note that the item is Journal Fee by IJICIC. If you would like to get the Receipt for the payment, please notify us via [office@icicelb.org](mailto:office@icicelb.org) and indicate the detailed Receipt Information as the following sample at the same time.

-----  
Name: \*\*\*\*

Organization: \*\*\*\*

Paper Title: \*\*\*\*  
-----

Yan Shi, Editor-in-Chief  
ICIC-ELB Editorial Office  
Tokai University, Kumamoto Campus  
9-1-1, Toroku, Kumamoto 862-8652, Japan  
Tel: +81-96-386-2666; Fax: +81-96-386-2666  
E-mail: [office@icicelb.org](mailto:office@icicelb.org)



Dear Editor of ICIC Express Letters, Part B: Applications

We would like to thank you for the Acceptance, and the opportunity to resubmit a revised copy of this manuscript. We would also like to take this opportunity to express our thanks to the reviewers for the positive feedback and helpful comments for correction or modification.

We believe have resulted in an improved revised manuscript, which you will find uploaded alongside this document. The manuscript has been revised to address the reviewer comments, which are appended alongside our responses to this letter.

We very much hope the revised manuscript is accepted for publication in Journal.

Sincerely yours,

Iwan Binanto  
*on behalf of the authors*

## REVISION NOTE

No.	Reviewer Notes	Comments
1.	The review on existing studies is not enough. It has been found that no reviewed references in the Introduction are published in recent three years; therefore, the motivation of this work, that is, why to explore mining pattern on Rodent Tuber's LC-MS data, will be limited.	<ul style="list-style-type: none"> <li>• Adding new reviewed references that published in recent three years.</li> <li>• The motivation is: <i>It is not trivial to processing this data to be useful information. Many techniques are used to process these data. It is challenging to extract the information contained in the LC-MS data. One of them is finding certain patterns in the data with Association Rule. This pattern can be used to find and recognize certain chemical compounds contained in other LC-MS data. Further, the association rule can be used in machine learning.</i></li> </ul>
2.	In the Introduction, the advantages of this study compared with the existing relevant studies should be highlighted, and the results obtained from this study should also be stated.	The revision is: <i>The results of this study will help biological or pharmaceutical scientists to 1) analyze and identify the possible presence of other compounds, 2) finding interesting relationships and/or casualities between compounds, 3) finding the frequent patterns, and 4) can be used for further processing in machine learning</i>
3.	The caption of Figure 2 is suggested to be improved as "Diagram of research method".	Done.
4.	Below Figure 5, authors mentioned the next step is dataset processing with form as a market basket transaction; however, what is the corresponding step in Figure 2?	We revised the sentence and make clear the corresponding step in Figure 2: <i>The next step is "Run FP-Growth Algorithm" which is processing the transactional form as a market basket transaction into FP-Growth algorithm.</i>
5.	To prove the effectiveness of the proposed system, a comparison with state-of-the-art studies is suggested to be added.	We agree there is a comparison with state-of-the-art study, however data characteristics are not the same. We worried this will be an inappropriate comparison.
6.	Not enough recently published references are cited in the manuscript; therefore, it is suggested to cite more up-to-date references from mainstream journals, for example, the	We agree to added the paper suggested by reviewers as reference.



	<p>paper titled “A Parallel Method for Mining Frequent Patterns with Multiple Minimum Support Thresholds” in International Journal of Innovative Computing, Information and Control, vol.15, no.2, pp.479-488, DOI: 10.24507/ijicic.15.02.479, 2019.</p>	
7.	<p>There are several ill-formed expressions existing in the manuscript, which need further improvement, such as "It find C49H79O13P is the dominant in the LC-MS data", "it is not generate candidate itemsets", "These papers are categorized as follow", "...in Python programming for generate sample" and "This process is conversion dataset to the form of market basket transaction as illustrated in Figure 4A and snippet the real result dataset of this conversion is shown".</p>	<p>We revised ill-formed expressions.</p>