A. Prasetyadi

The effect of chassis weight optimization on the carbon footprint of the electric prototype vehicle

Assignment 2 Part 1 (Moodle TT)

Skripsi E (TM I/2024/2025) (Moodle TT)

Universitas Sanata Dharma

Document Details

Submission ID 6 Pages trn:oid:::1:3027405958 2,198 Words Submission Date Oct 2, 2024, 3:14 AM GMT+7 Download Date Oct 2, 2024, 3:22 AM GMT+7 File Name

 $8233_A._Prasetyadi_The_effect_of_chassis_weight_optimization_on_the_carbon_footprint_of_the_....pdf$

File Size

1.8 MB

11,369 Characters

0% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely AI-paraphrased.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Detection Groups

1 AI-generated only 0% Likely AI-generated text from a large-language model.

2 AI-generated text that was AI-paraphrased 0% Likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

Disclaimer

Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (it may misidentify writing that is likely AI generated as AI generated and AI paraphrased or likely AI generated and AI paraphrased writing as only AI generated) so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?

The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted

What does 'qualifying text' mean?

assignment in accordance with their school's policies.

Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.



The effect of chassis weight optimization on the carbon footprint of the electric prototype vehicle

Heryoga Winarbawa^{1*} and Andreas Prasetyadi¹

¹Mechanical Engineering Department, Faculty of Science and Technology, Sanata Dharma University, Sleman, Indonesia

Abstract. Electrification of vehicles has become increasingly widespread lately. It aims to reduce carbon emissions globally. Another step, namely reducing vehicle weight, is expected to reduce energy consumption during the operation. A vehicle part that can be reduced in weight is the chassis. This research compares the carbon footprint between the stock chassis and the lightweight version. The lightweight chassis requires additional energy during its fabrication. Life cycle analysis (LCA) is conducted to calculate the carbon footprint of each chassis. Material loss and manufacturing time are the main differences in the footprint. Manufacturing strategy is important in order to minimize the emission of the process. The lightweight chassis can reduce CO_2 emission by 11% assuming 200 hours of operation. Therefore, optimization of the weight significantly reduces the emission.

1 Introduction

Electric vehicles are considered to be a solution for transportation fit into climate action. In dominated coal and hydropower electricity, the electricity vehicles can reduce emissions by 37% and 90%, respectively [1]. Such transportation modes have less carbon emission than internal combustion ones. The electric vehicles have higher direct efficiency than internal combustion vehicles. Electric motor is generally more efficient than diesel and petroleum engines. The electric vehicles reduce fuel transportation. The fuel for electricity just needs transportation from the source to the power plant. A green and clean grid is very positive to lower the emission. The battery capacity and electric intensity are also other factors of emission reducer. Specific travel requirement is important to make emission reduction real [2]. All of the aforementioned factors are external. The fewer moving parts number of the electric vehicles than internal combustion is the factor. However, it also has drawbacks due to battery requirements. The battery tends to be the heaviest part of the vehicle [3].

Lightweight is the key to the electric vehicle. Variation of the vehicle weight depends only on the load of the vehicle during its travel. It is different from an internal combustion vehicle that has fuel as another variable changing during its movement. The energy consumption of the electric vehicle depends on the unladen weight of the vehicle [1]. Heavier vehicle needs more energy for every kilometer travel. Therefore, it is important to make the

turnitin Page 3 of 8 - AI Writing Submission

Submission ID trn:oid:::1:3027405958

© The Authors, published by EDP Sciences. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

^{*} Corresponding author: heryoga@usd.ac.id

electric vehicle as light as possible. Among the parts, chassis is the unladen weight that contributes significantly to the total weight of the vehicle.

Chassis weight optimization is important for better electric vehicles. An excellent chassis provides safety and performance. One of the criteria of a vehicle chassis is its weight. The weight of the chassis can affect significantly the vehicle's performance due to tractive force requirement. In addition to gradient, and aerodynamic, the rolling force is dominated by its weight [4]. Therefore, it is clear that the weight of the chassis affects the emission operationally.

The emission of a vehicle depends on some factors in LCA. The factors include upstream, operational, and downstream cycles. A study of upstream factors was conducted by Yao, et al. [1]. Analysis of the fuel for all processes was also reported in China [2]. While the study of subsidies to meet the emission of China was the work of Zou et al. [3]. However, a detailed study of chassis effect to emission was not available yet.

The aim of this research is to find out how significantly the carbon footprint is reduced by optimizing the chassis weight of a prototype electric vehicle. The work will be presented in 4 sections. The introduction starts the presentation to show the state of the art of study. The methods show the steps of data collection and chassis model. Results and discussion become the third part. The final part is the conclusion showing some found of the work.

2 Methods

Basic of LCA of energy and material used for the chassis fabrication will be estimated for the carbon footprint. The data of the energy for production uses PLN report of 2022. The emission of the energy is calculated using energy mix of the PLN and energy need for the production of the chassis. The energy for production consists of energy for material production and manufacturing production. The operational energy consumption is estimated in the form of the difference.

2.1 Energy mix footprint

Indonesia Electricity Company (PLN) produced 273,761 GWh. The primary energy of the electricity consists of diesel fuel, coal, natural gas, geothermal, water, biomass, solar, and wind. The distribution of primary energy usage for electricity generating is presented in Table 1. The CO_2 emission equivalent for electricity generation was reported 663.5 gr/kWh [5].

Type of energy	Generated Electricity (GWh)	percentage
Oil Fuel	17,186	5.58
Coal	192,563	62.52
Natural Gas	68,315	22.18
Geothermal	6,899	2.24
Hydro	1,016	7.48

Table 1.	Electricity	Generation	according to	energy type.

2.2 Chasis CO₂ Emission Footprint

Chassis CO₂ emission footprint consists of emission of metal production, manufacturing process, and metal destruction. The steel production emission was reported 1215.17 kg CO₂ equivalent/ton [6]. The aluminium CO2 equivalent emission was 7.15 ton/ton aluminium as the mean number [6]. In addition to steel production, the manufacturing consists cutting process, and welding process. The emission of chasis can be calculated using equation (1) as follow. The E_{CO2T} , E_{CO2P} , E_{CO2M} , and E_{CO2D} are CO₂ equivalent emission of chasis, material production, manufacturing process, and demolishing, respectively. The manufacturing process is composed of cutting and welding. Therefore, the emission of the manufacturing the cutting and welding emission respectively. The demolishing of the metal, as it is recyclable, the number applies percentage of metal production using recycle material which is 10% [6]. The metal production and its scrapping can be calculated using equations (6) and (7) respectively.

$E_{CO2T} = E_{CO2P} + E_{CO2M} + E_{CO2D}$	(1)
$E_{CO2M} = E_{CO2cut} + E_{CO2weld}$	(2)
$E_{CO2cut} = Energy cutting (kWh) * 0.6635 kg$	(3)
$E_{CO2weld} = Energy welding(kWh) * 0.6635 kg$	(4)
$E_{CO2M} = Operationtime * E * 0.6635 kg$	(5)
$E_{CO2P} = Mass material (kg) * 7.15 kg$	(6)
$E_{CO2D} = Mass material (kg) * 0.715 kg$	(7)

3 Results and discussion

The complete chassis consists of 3 sections, the main chassis, front arm, and rear sub-frame. Each chassis section fabrication is then analyzed for its energy usage requirements. Energy consumption when fabricating each chassis is divided into 2 main parts. First, the preparation of each component for the welding process, such as cutting, drilling, and grinding, and the final step is the welding process itself. Then, the chassis is arranged in such a way as to form a vehicle that can operate. Energy consumption when the vehicle is operating is also then analyzed, which is then totaled by energy use during fabrication. The total energy used during chassis fabrication and when the vehicle is in operation is then converted into CO_2 equivalent.

3.1 Energy consumption for cutting, drilling, and grinding

The first step of fabricating a chassis is cutting the aluminum square tubing, round tubing, and sheet to the required as needed according to the design. For square and round tubing, a 1,7 kW miter saw is used to cut straight or at an angle. For aluminum sheets, the most effective way to cut is using a 3,3 kW laser cut machine. 0,9 kW machine is used for drilling operations. 0,67 kW angle grinder is used for grinding operations.

The general formula to calculate the energy consumption of each process as written in Equation (8)

$$E = P.t \tag{8}$$

Where E is energy consumption, P is the power of the machine used, and t is processing time.

The energy consumption for the first step in fabricating the chassis is then put together in the table 2.

	Energy Consumption (kWh)		
Chassis Section	Chassis - Stock	Chassis - Lightweight	
Main Chassis	0,0255	0,0596	
Front Arm	0,0279	0,0645	
Rear Sub-Framee	0,0818	0,0759	
Total	0,1353	0,2000	

Table 2. Energy consumption for cutting, drilling, and grinding.

3.2 Energy consumption for TIG welding

The final process for making a chassis is to combine each component that has been previously processed using a welding process. The TIG welding process is commonly used to weld aluminum. 6,1 kW TIG welding machine is used in this process.

The power and total energy consumption for TIG welding written in Equation (9) and (10), respectively

$$P = (V_{output} . I_{output}) / efficiency$$
(9)

$$E = P.t$$
(10)

Wolding Decours	Energy Consumption (kWh)		
weiding Process	Chassis - Stock	Chassis - Lightweight	
Main Chassis	1,433	0,373	
Front Arm	0,442	0,317	
Rear Sub-Chassis	1,711	0,312	
Total	3,586	1,002	

Table 3. Energy consumption for TIG welding.

3.3 Energy consumption while the vehicle is operating

Simulation of energy consumption (in Joule) when both vehicles are operating is then compared using Equation (11), and then converted to energy consumption (in kWh) using Equation (12). The difference between both vehicles is the mass of the vehicle, while the other specifications are the same. Vehicle specifications and energy usage results are shown in the table.

$$E_{j} = (\mu.m.g.Cos\Theta) + (m.g.Sin\Theta) + (0,25.C_{d}A.\rho.(v_{i}^{2}+v_{f}^{2}).d) + (0,5.m.(v_{i}^{2}+v_{f}^{2}))$$
(11)

$$E_{Wh} = E_{j}.0,000278$$
(12)

G	Vehicle Chassis Type		
Spesifications	Chassis - Stock	Chassis - Lightweight	
Mass of vehicle, <i>m</i> (kg)	94,3	84,2	
μ	μ 0,		
Gravitational acceleration, g (kg/m ²)	9,8		
Road elevation, Θ (°)	0		
Coefficient of drag of vehicle, Cd	0,15		
Frontal area of vehicle, $a (m^2)$	0,37		
Density of air, ρ	1,293		
Initial speed of vehicle, v_i (m/s)	8,5		
Final speed of vehicle, $v_f(m/s)$	0		
Diameter of vehicle's wheel, d (mm)	100		
Energy consumption, E (J)	3539,90	3174,64	
Energy consumption, E (kWh)	0,98 0,88		

Table 4. Cha	assis spe	cification.
--------------	-----------	-------------

3.4 The emission

The CO₂ emission for both chassis from fabrication to demolishing can be shown in Table 5.

 Table 5. Emission of the chasis life cycle.

Cycle	Emission (kg)	
	Chasis Stock	Lightweight Chasis
Material Production	674,245	602,03
Manufacturing Process	2,469	0,798
Operation	130,046	116,776
Demolishing	67,424	60,203
Total Emission	874,185	779,806

Table 5 shows the emission of the chassis life cycle. It mentions that the material dominates the chassis emission. The second emission contributor is the operation assuming 200 hours of operation for the training and competition. Manufacturing is the least significant contributor to the emission. In the transportation sector, electric vehicles will help to reduce carbon emissions [7]. In general, increasing vehicle weight causes an increase in total carbon emissions [8]. The electric vehicles that powered by battery dan recharged using renewable energy resources is producing the lowest amount of total life-cycle emission [9]. The larger weight of electric vehicle compared to internal combustion electric vehicle (hybrid) cause 59% more CO_2 emissions [10]. Therefore, optimization of the chassis weight prototype electric vehicle has a great impact on the total CO_2 emission.

4 Conclusion

The lightweight chassis can reduce CO_2 emission by 11% assuming 200 hours of operation. The stock chassis has 874.2 CO_2 emissions, while the lightweight has 779.8 kg. The material is the main contributor to the emission. Therefore, optimization of the chassis weight significantly reduces the emission.

References

- 1. R. Wang, Y. Song, H. Xu, Y. Li, and J. Liu, Energies 15, 1 (2022)
- M. Zou, M. Liu, D. Liu, H. Jia, S. Su, X. Peng, Y. Zhang, and S. Shang, IOP Conf. Ser. Earth Environ. Sci. 791, (2021)
- 3. L. Yao, N. Ma, B. Liu, and H. Shi, E3S Web Conf. 385, (2023)
- 4. A. K. Maurya, Ind. Eng. (2023)
- 5. Indonesia: emissions intensity from electricity generation (2022)
- S. Alyarahma, I. P. Sari, and W. Kurniawan, IOP Conf. Ser. Earth Environ. Sci. 1203, (2023)
- 7. Z. Gao, H. Xie, X. Yang, L. Zhang, H. Yu, W. Wang, Y. Liu, Y. Xu, B. Ma, X. Liu, and S. Chen, Carbon Neutralization 528 (2023)
- 8. Y. Li, N. Ha, and T. Li, Energies 12, (2019)
- 9. J. Buberger, A. Kersten, M. Kuder, R. Eckerle, T. Weyh, and T. Thiringer, Renew. Sustain. Energy Rev. **159**, 112158 (2022)
- 10. Q. Qiao, F. Zhao, Z. Liu, S. Jiang, and H. Hao, Energy Procedia 105, 3584 (2017)